

Mini Soundproof Booth

Internal in acoustic foam



- Complies with ISO 8253 1:2010*
- The smallest, lightweight and portable soundproof booth
- Designed for hearing screening in audiology centres
- Ready to be used in a few minutes
- Available in DIY kit with reversible door and magnetic closing.

Configuration PRO 25



Configuration PRO 25 SLIM



Folding table and connecting



All our cabins offer the best of Italian design



Product conforms with directive EEC/93/42 regarding class I medical devices

Technical specification

Available sizes

Code	Outside Dimensions (LxWxH)	Inside Dimensions (LxWxH)	Ext. sq.m	Weight
P25	96 x 96 x 197 cm	81 x 81 x 180 cm	0.92	198 Kg
P25SLIM	96 x 74 x 208 cm	81 x 60 x 180 cm	0.71	171 Kg

PRO25 SLIM has been designed to pass through standard doors with a width of 830 mm. Equipped with 4 castors (2 with brake) which allow anyone to move it easily.

Applications

PRO25 line is recommended for hearing screening in audiology centers and shops for those who have limited space available and need a very small soundproof booth. These booths can be also used in temporary situations for occupational medicine, in companies and schools. Basic noise reduction booth, ideal for a quiet environment.

Exterior

The exterior finishing is made of a white, highly-resistant, fireproof, washable panel.

Interior

The interior finishing is made of acoustic pyramid foam in anthracite grey, designed to reduce sound waves for a perfect acoustics.

Door

The door is reversible with magnetic closing. The opening (right or left) can be decided upon assembling the booth and changed in 5 minutes. Clear opening 55 x 168 cm (w x h).

Window

The window consists of a special double safety glass. Clear view 56x56 cm (w x h).



Floor

The floor is layered with different materials and it stands on anti-vibration adjustable feet. Finishing: technical, antistatic, fireproof, washable carpet.

Connecting instruments

Cables are laid through a new universal soundproof panel without jack connection. All kinds of cables can be used without the need to be cut. Adaptable to all types of instruments. Hangers for earphones are included.

Electrical system

Lighting is ensured by a fluorescent lamp with low energy consumption. Power supply: 220/240 V. 50-60 Hz.

Noise reduction PRO25 line is tested at the Technical-Physics Laboratory C.S.I. S.p.A. (Milano-Italy) accredited by ACCREDIA. *Product conforms with international UNI EN ISO 8253 1:2010 with a background noise no greater than 58dB (at 500Hz) assuming a noise barrier headset (audiocups) is used.

Acoustic insulation

Hertz	125	250	500	1000	2000	3150	4000	6300	8000
dB	18.0	16.0	26.7	30.8	28.8	30.0	30.9	38.0	39.0

Optional Equipment

- External folding table (79 x 50 cm)
- Internal folding table (79 x 32 cm)
- Audiocups
- Kit 10 or 6 jack cable extensions
- Jack panel (10 jack + USB)
- Modification Voltage 110 V.
- Vertical window strip (16 x 115 cm)
- Wall audiometer support
- Internal seat
- Kit 4 castors (2 with brake)

Installation

Easy and quick to install; no specialized staff required. Just follow the instructions. Thanks to reduced weight and small size can be easily set up in 5 minutes and transported in a Station Wagon car.

Notes

The materials are fireproof and self-extinguishing at the origin. Specifications are subject to change without notice. Warranty: limited to one year from delivery date.

Packaging

Delivered for shipping in a ISPM wooden case with DIY kit

Standards

Medical Device Class I - MDD 93/42/CEE
2007/47/CE - CEI 64/11
CEI 64/8 - 2006/95/CE
UNI EN ISO 8253 1:2010.

